FINISH SCHEDULE

FLOOR COMMERCIAL SHEET VINYL	BASE 4' CONTINUOUS SELF-COVE UP VALL OR UP TOEKICK OF COUNTER OR EQUIPMENT THAT SETS FLUSH ON THE FLOOR ****	WALL PAINTED GYPSUM BDARD SMOOTH LIGHT COLOR SEMT-GLOSS ENAMEL W/ F.R.P. BDARD BEHIND	CEILING T-BAR V/ ACQUISTIC CEILING TILE. SMODTH, NON- ABSORBENT, AND
	UP WALL OR UP TOEKICK OF COUNTER OR EQUIPMENT THAT SETS FLUSH ON THE	SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL W/	TILE. SMOOTH, NON-
		ALL SINKS (MIN. 8' HIGH)	WASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
CONTINUOUS E.G. QUARRY TILE	4" SELF COVING QUARRY TILE	F.R.P. BOARD, ETC.	CEILING TILE SMOOTH. NON- ABSORBENT, AND WASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
CONTINUOUS E.G. QUARRY TILE	4" SELF CDVING GUARRY TILE	FULL HEIGHT F.R.P. BOARD TO CEILING OR TO EXHAUST HOOD	CEILING TILE SMOOTH, NON- ABSORBENT, AND VASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
CONTINUOUS E.G. QUARRY TILE TO EXTEND AT A MINIMUM 3" TO DPEN SIDE	IF NOT ON 6' LEGS THEN USE QUARRY TILE COVED BASE UP TO THE TOE KICK QUARRY TILE	F.R.P. BOARD ETC.	CEILING TILE SMOOTH. NON- ABSORBENT, AND WASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
CONTINUOUS E.G. QUARRY TILE	4' SELF CO∨ING QUARRY TILE	8″ MIN. F.R.P. B⊡ARD	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL
CONTINUOUS E.G. QUARRY TILE	4' SELF CD∨ING QUARRY TILE	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL V/ 4" MIN. CERAMIC TILE OR F.R.P., BOARD WAINSCOTING	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL
V.С.Т. жж	4' TOP SET##	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL	CEILING TILE SMOOTH NON- ABSORBENT, AND WASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
COMMERCIAL SHEET VINYL	4" SELF COVING SHEET VINYL	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL	PAINTED GYPSUM BDARD SMDDTH LIGHT COLDR SEMI-GLOSS ENAMEL
SEALED CONCRETE	4' CONTINUOUS SELF- COVE (ALUMINUM METAL BASE)	MANUFACTURE PRE-FABRICATED G.I. PANEL	MANUFACTURE PRE-FABRICATED G.I. PANEL
COMMERCIAL SHEET VINYL	4' SELF COVING SHEET VINYL	PAINTED GYPSUM BOARD SMOOTH LIGHT COLOR SEMI-GLOSS ENAMEL	T-BAR W/ ACOUSTIC CEILING TILE. SMOOTH, NON-ABSORBENT, AND WASHABLE SAMPLE TO BE SUBMITTED FOR APPROVAL PRIOR TO INSTALLATION
CONTINUOUS E.G. QUARRY TILE	4' SELF COVING QUARRY TILE	F.R.P. TO BE INSTALLED IN ALL VET AREAS	
V.T.C. ##	4' TOP SET **	COMMERCIAL INTERIOR FINISHES	T-BAR W/ ACCUSTIC CEILING TILE OR OTHER COMMERCIAL CEILING FINISHES
CARPET	4' TOP SET **	COMMERCIAL INTERIOR FINISHES	T-BAR V/ ACCUSTIC CEILING TILE OR OTHER COMMERCIAL CEILING FINISHES
	E.G. GUARRY TILE CONTINUOUS E.G. GUARRY TILE CONTINUOUS E.G. GUARRY TILE TID EXTEND AT A MINIMUM 3" TID DEN SIDE CONTINUOUS E.G. GUARRY TILE CONTINUOUS E.G. GUARRY TILE CONTINUOUS E.G. GUARRY TILE COMMERCIAL SHEET VINYL SEALED CONCRETE COMMERCIAL SHEET VINYL CONTINUOUS E.G. GUARRY TILE V.T.C. ***	E.G. QUARRY TILE CONTINUOUS E.G. QUARRY TILE CONTINUOUS E.G. QUARRY TILE CONTINUOUS E.G. QUARRY TILE CONTINUOUS E.G. QUARRY TILE TID EXTEND AT A MINIMUM 9' TID BASE UP TO THE TOE KICK QUARRY TILE CONTINUOUS CONTINUOUS E.G. QUARRY TILE CONTINUOUS E.G. QUARRY TILE 4' SELF COVING QUARRY TILE CONTINUOUS E.G. QUARRY TILE 4' SELF COVING QUARRY TILE COMMERCIAL 4' SELF COVING SHEET VINYL SEALED CONCRETE COMMERCIAL 4' SELF COVING SHEET VINYL SEALED CONCRETE COMMERCIAL 4' SELF COVING SHEET VINYL COMMERCIAL 4' SELF COVING SHEET VINYL CONTINUOUS E.G. QUARRY TILE 4' SELF COVING SHEET VINYL CONTINUOUS 4' SELF COVING SHEET VINYL CONTINUOUS 4' SELF COVING GUARRY TILE CONTINUOUS 4' SELF COVING GUARRY TILE CONTINUOUS 4' SELF COVING GUARRY TILE CONTINUOUS 4' SELF COVING QUARRY TILE	E.G. GUARRY TILE CONTINUOUS 4' SELF COVING GUARRY TILE CONTINUOUS E.G. GUARRY TILE COMMERCIAL 4' TOP SET MX COMMERCIAL 4' SELF COVING SHEET VINYL CONTINUOUS E.G. C

NDTE: ALL WALLS AND CEILING MUST BE 70% LIGHT-REFLECTED

F.R.P. MEANS FIBER GLASS REINFORCED PANELS

- ** IF NO PLUMBING FIXTURES IN RODM.

 *** A RODM VHERE FOOD IS STORED DNLY IN UNDPENED BOTTLES, CANS, CARTONSACKS, OR OTHER ORIGINAL SHIPPING CONTAINERS.
- ***** IF UNABLE TO COVE UP TO THE EQUIPMENT THEN A CURB (MIN.2') IS TO BE CONSTRUCTED TO SET THE EQUIPMENT ON.

 DNCE CURVE IS CONSTRUCTED, THEN COVE THE FLOOR MATERIAL UP THE CURB VITH A MIN. 3/8' RADIUS COVE.